

DEFOAMER MS-D

INDUSTRIAL STRENGTH DEFOAMING AGENT FOR AQUEOUS METALWORKING FLUIDS

DEFOAMER MS-D is a high performance antifoam agent designed for tankside addition in metalworking fluid systems.

DEFOAMER MS-D is completely water-dispersible and will not adhere to metal surfaces. The use of this product will not impair subsequent finishing operations such as painting or plating.

PROPERTIES

Appearance	Translucent, off-white liquid
Odor	Essentially odorless
Specific Gravity @ 60° F.	1.03 - 1.07
Lbs./Gallon	8.5 - 9.0
Flash Point, PMCC, ° C.	204

RECOMMENDED USE

DEFOAMER MS-D is intended to be used as a tankside additive to control foam in water-extensible metalworking fluids. Add between 1 and 2 fluid ounces DEFOAMER MS-D for each 100 gallons of fluid in system.

For best results, dilute into 1 pint of water before adding to sump. Add slowly into an area of high coolant flow for best dispersion.

Material Safety Data Sheets are available for all products.

All reasonable care has been taken to ensure that the above information is accurate as of the date of printing.

6/01



36 Draffin Road, Hilton, NY 14468 Phone: 800-828-6351 585-392-3434 Fax: 585-392-2691
EMERGENCY NUMBERS: CHEMTREC (800) 424-9300 Monroe Fluid Technology (800) 828-6351
Website: <http://www.monroefluid.com>