



Safety Data Sheet in accordance with Regulation (EU) No. 453/2010 and OSHA 29 CFR 1910.1200 HCS

ASTRO-CUT HP XBP

1. Identification of the Substance/ Mixture and of the Company/ Undertaking

Product Name: ASTRO-CUT HP XBP

Preparation Date: May 27, 2015
Revision Date: April 5, 2016

Recommended Use: Metalworking Fluid

Supplier: MONROE FLUID TECHNOLOGY
36 Draffin Road,
Hilton, NY 14468

Phone: 800-828-6351 585-392-3434

EMERGENCY NUMBERS: CHEMTREC (800) 424-9300 Monroe Fluid Technology (800) 828-6351

2. Hazards Identification

GHS Classification:

Eye Irritant – Category 2
H320: Causes eye irritation
Skin Irritant – Category 2
H315: Causes skin irritation

GHS Labeling:

Symbols:



Signal Word: Warning

Precautionary Statements:

P264: Wash thoroughly after handling
P280: Wear protective gloves/ protective clothing/ eye protection
P302 + P352: IF ON SKIN, wash with soap and water
P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313: If skin irritation occurs, get medical advice/attention
P337 + P313: If eye irritation persists, get medical advice/attention
P362: Take off contaminated clothing and wash before reuse

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] and OSHA 29 CFR 1910.1200

HCS: Skin Irritant – Category 2, Eye Irritant – Category 2



Safety Data Sheet in accordance with Regulation (EU) No. 453/2010 and OSHA 29 CFR 1910.1200 HCS

ASTRO-CUT HP XBP

Other Hazards Not Classified: No significant hazards

3. *Composition/Information on Ingredients*

Mixture: Base oil, emulsifiers and additives.

Chemical Name	CAS Number	Concentration, Wt. %
3-iodo-2-propynyl Butyl Carbamate	55406-53-6	Trade secret
Triethanolamine	102-71-6	Trade secret
Monoisopropanolamine	78-96-6	Trade secret
1,2-Benzisothiazolin-3-one	2634-33-5	Trade secret
Base oil	Varies	Trade secret

4. *First Aid*

Inhalation: If inhaled, move to fresh air. If victim has stopped breathing give artificial respiration, preferably, mouth to mouth. Contact a physician immediately.

Eyes: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention

Ingestion: Do not induce vomiting. Contact a physician immediately.

Skin: IF ON SKIN, wash with soap and water. If skin irritation occurs, get medical advice/attention. Take off contaminated clothing and wash before reuse

5. *Fire-fighting Measures*

Suitable extinguishing media: Carbon dioxide, Dry chemical, Alcohol foam

Specific hazards: None

Specific protective equipment and precautions for fire fighters: Isolate fire area and deny unnecessary entry. Use dry chemical, alcohol foam or carbon dioxide. Water may be ineffective but should be used to keep fire exposed containers cool. If a spill or a leak has not ignited, use water spray to disperse the vapors. Water spray may be used only to keep fire exposed containers cool, protect personnel attempting to stop leak and disperse vapors.

Unusual Fire and Explosion Hazards: None

Flammability Properties:

Flash point: None

Method Used: PMCC

6. *Accidental Release Measures*

Personal precautions, protective equipment and emergency procedures:

Use personal protective equipment. Ensure adequate ventilation.



Safety Data Sheet in accordance with Regulation (EU) No. 453/2010 and OSHA 29 CFR 1910.1200 HCS

ASTRO-CUT HP XBP

Environmental Precautions: Do not allow spilled material to enter sewers or streams. If material is released, indicate that there is a risk of slipping in the area. If spills are likely to enter any drain, waterway or groundwater, contact the appropriate governmental agency.

Methods and materials for containment: Add dry material to absorb (if large spill, dike to contain). Using recommended protective equipment, pick up bulk of spill and containerize for recovery or disposal. Flush area with water to remove residues.

7. Handling and Storage

Precautions for safe handling: Read label for instructions in use of product. Prevent small spills and leakage to avoid slip hazard. Avoid contact with skin, eyes and clothing. Do not wear contact lenses when handling this product. Keep out of the reach of children. Wash thoroughly after handling. Material can accumulate static charges which may cause an electrical spark (ignition source).

Conditions for safe storage: Store in closed containers in a cool, dry well ventilated area not exposed to sunlight. Maintain closure of bungs. Do not reuse container. Avoid container damage while storing. Do not allow material to be stored below OC. Do not allow material to freeze. Empty containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, bronze, solder, drill, grind or expose such containers to heat, flame, sparks, static electricity or other sources of ignition; they may explode and cause injury or death. Do not attempt to refill containers since residue is difficult to remove. Empty drums should be completely drained, properly bunged and returned to a drum reconditioner. All containers should be disposed of in an environmentally safe manner in accordance with governmental regulations.

8. Exposure Controls/Personal Protection

Control parameters:

Exposure Guidelines: Triethanolamine ACGIH TLV: 5 mg/m³ Base oil: (Mist) OSHA PEL: 5 mg/m³

Appropriate engineering controls: Proper protection and controls is dependent upon the potential exposure conditions. No special requirements are needed under ordinary conditions where adequate ventilation is available.

Individual protective measures:

Respiratory protection: General room ventilation should be satisfactory. Exhaust ventilation may be necessary if misting is generated.

Eye protection: Safety glasses with shields or chemical goggles are required. Contact lenses should not be worn if the product could be splashed into the eyes.

Hand protection: Rubber gloves are required for single, short duration exposures and for prolonged or repeated exposures.

Body protection: For single, short duration and for prolonged or repeated exposures to the skin, wear impervious, protective clothing including rubber safety shoes to avoid skin contact.

9. Physical and Chemical Properties

Appearance: Amber liquid



Safety Data Sheet in accordance with Regulation (EU) No. 453/2010 and OSHA 29 CFR 1910.1200 HCS

ASTRO-CUT HP XBP

Odor: Bland

Odor Threshold: N/A

pH : @ 5% in water: 9.8 +/- 0.3

Melting point/freezing point: 0°C

Initial boiling point and boiling range: >105°C

Flash Point (PMCC): None

Evaporation Rate: Not determined

Flammability (Solid, Gas): N/A

Upper/lower flammability or explosive limits: UEL: Not determined LEL: Not determined

Vapor pressure: <1 mm Hg @ 20°C

Vapor density: Not determined

Relative density: 1.01 +/-0.01

Partition coefficient n-octanol/water: Not determined

Autoignition Temperature: No data available

Decomposition Temperature: Not determined

Viscosity: Not determined

10. Stability and Reactivity

Chemical stability: Stable at normal conditions

Possibility of hazardous reactions: Not expected and hazardous polymerization will not occur

Conditions to avoid: Excessive Heat.

Incompatible Materials: None known.

Hazardous decomposition products: Oxides of carbon, nitrogen and phosphorus.

11. Toxicological Information

Inhalation: Inhalation of vapors or mist can be irritating to respiratory passages

Skin: Causes skin irritation

Eyes: Causes eye irritation

Oral: None known

Systemic (other target organ) Effects: None known

Teratology (birth defects): None known

Reproductive Effects: None known

Mutagenicity (effects on genetic material): None known

Carcinogenicity: IARC: NO NTP: No OSHA: No

12. Ecological Information

Persistence and degradability: Data is not available.

13. Disposal Considerations



Safety Data Sheet in accordance with Regulation (EU) No. 453/2010 and OSHA 29 CFR 1910.1200 HCS

ASTRO-CUT HP XBP

Disposal methods: P501: Dispose of contents/ container to an approved waste disposal plant
Dispose of in accordance with federal, state and local regulations

Precaution for disposal: All recovered material should be packaged, labeled, transported and disposed or reclaimed in conformance with Good Engineering Practices. Comply with all applicable governmental regulations. Avoid landfilling of liquids. Reclaim where possible.

14. Transport Information

US DOT: Not regulated by the US DOT

RID/ADR: Not regulated by RID/ADR

IMO: Not regulated by IMO

IATA: Not regulated by IATA

15. Regulatory Information

US TSCA: In compliance with the inventory

Canada DSL: In compliance with the inventory

Cal. Prop. 65 This product does not intentionally contain any chemicals known by the State of California to cause cancer and/or birth defects. Moreover, we do not routinely analyze its products for impurities which may be such chemicals.

SARA Section 313 This material contains no chemicals subject to the supplier notification requirements of the SARA 313 Toxic Release Program.

VOC Content (SCAQMD ASTM 1868-10) : <100 g/l concentrate; <10 g/l at maximum recommended dilution of 10%.

16. Other Information

Special Precautions to be Taken in Handling and Storage:

Normal precautions common to good manufacturing practices should be followed in handling and storing. Store away from food. Wash hands before eating, drinking or smoking. Use as directed.

Disclaimer: This document has been prepared in good faith and from information provided to us by our suppliers and other sources considered to be reliable. No warranty, express or implied is given. The buyer is responsible to evaluate all available information when using this product for any particular use. The buyer is also responsible for complying with all Federal, State, Provincial, and Local Laws and regulations when using this product.