



36 Draffin Road Hilton, New York 14468  
Phone: 585-392-3434  
Toll Free: 1-800-828-6351  
Sales: sales@monroefluid.com  
Technical: technical@monroefluid.com

## ASTRO-CUT MICRO EP-XBP

### Overview

ASTRO-CUT MICRO EP-XBP is a heavy duty BIOSTABLE semi-synthetic high pressure metalworking coolant. ASTRO-CUT MICRO EP-XBP combines the superior chemical flexibility of synthetics with mineral oil and a chlorinated extreme-pressure additive. ASTRO-CUT MICRO EP-XBP has exceptional foam control, hard water stability and tramp oil rejection. It provides outstanding extreme-pressure lubricity for machining and grinding virtually all metals, particularly Aluminum, Stainless Steels and other hard to machine alloys. ASTRO-CUT MICRO EP-XBP is not recommended for use on Magnesium. ASTRO-CUT MICRO EP-XBP does not contain DCHA.

### Applications

ASTRO-CUT MICRO EP-XBP is designed for use in high and low pressure metal removal operations such as all CNC milling, turning, drilling, tapping, grinding and sawing.

### Recommended Concentration

Application	Concentration, %	Ratio	Refractometer
Milling, Drilling, Turning	5%	1:20	4.5
Centerless, ID, OD, Surface Grinding	4%	1:25	3.6
Tapping, Sawing, Reaming	10%	1:10	8.9

### Mixing

Concentration, %	4%	5%	6%	7%	8%	9%	10%
Ratio	1:25	1:20	1:17	1:14	1:12	1:11	1:10
Refractometer	3.6	4.5	5.3	6.2	7.1	8.0	8.9

When mixing coolant, it is best to use an automatic proportioner which accurately and thoroughly mixes coolant. To maintain recommended concentration, make-up or top-off should be added at one-half of the desired concentration. Never add concentrate directly to the machine; this could cause inverted emulsions.

### Typical Properties

Appearance-Concentrate	Amber liquid
Appearance- Dilution	Translucent Amber
Residual Film	Soft, fluid
pH @ 20:1	9.4 ± 0.2
Specific Gravity @ 60°F	1.01± 0.03
Lbs/Gallon	8.43 ± 0.1
Total Chlorine, wt %	3 – 5% max
Total Sulfur, wt %	1 – 2%
Flash point, PMCC	None

Material Safety Data Sheets are available for all products.  
All reasonable care has been taken to ensure  
that the above information is accurate as of the date of printing.