



36 Draffin Road Hilton, New York 14468
Phone: 585-392-3434
Toll Free: 1-800-828-6351
Sales: sales@monroefluid.com
Technical: technical@monroefluid.com

Astro-Cut High Pressure

Overview

ASTRO-CUT HIGH PRESSURE is a BIOSTABLE semi-synthetic high pressure metalworking coolant containing approximately 15% mineral oil. ASTRO-CUT HIGH PRESSURE has exceptional foam control, hard water stability and tramp oil rejection while providing outstanding lubricity for machining and grinding. It is compatible with virtually all metals except Magnesium and is formulated without the use of Chlorine.

Applications

ASTRO-CUT HIGH PRESSURE is designed for use in high and low pressure metal removal operations such as all CNC milling, turning, drilling, tapping, grinding and sawing.

Recommended Concentration

Application	Concentration	Ratio	Refractometer
Miling, Driling, Turning	5%	1:20	2.5
Centerless, ID, OD, Surface Grinding	4%	1:25	2.0
Tapping, Sawing, Reaming	10%	1:10	5.0

Typical Properties

Appearance-Concentrate	Amber liquid
Appearance- Dilution	Translucent Amber
Residual Film	Soft, fluid
pH @ 20:1	9.2 ± 0.2
Specific Gravity @ 60°F	1.02 ± 0.03
Lbs/ gal	8.51 ± 0.1
Total Sulphur, wt %	None
Total Chlorine, wt %	None
Flash point, PMCC	None

Material Safety Data Sheets are available for all products.
All reasonable care has been taken to ensure
that the above information is accurate as of the date of printing.