



36 Draffin Road Hilton, New York 14468  
Phone: 585-392-3434  
Toll Free: 1-800-828-6351  
Sales: sales@monroefluid.com  
Technical: technical@monroefluid.com

## MONROE CUT 240 CFS

### Overview

MONROE CUT 240 CFS is a general purpose cutting oil designed for use in screw machines, deep hole drilling, gun drilling or other machining applications that require the use of neat cutting oils. MONROE CUT 240 CFS can be used to machine the most difficult metals. It is formulated with chlorinated and sulfurized additives, making it especially suited for machining difficult alloys.

### Applications

MONROE CUT 240 CFS can be used for turning, broaching and other operations on most ferrous metals. This product should not be used on copper or its alloys due to the potential for staining.

### Features Benefits

- Enhanced Corrosion Inhibition
- Outstanding Lubricity for Superior Finishes
- EP Additives for Enhanced Performance
- Operator Friendly and Clean Running

### Recommended Concentration

Use MONROE CUT 240 CFS as received. Do Not mix MONROE CUT 240 CFS with water.

### Mixing

### Typical Properties

Appearance	Brown clear liquid
Odor	Mild, Fatty Odor
Chlorine	Present
Sulfur	Present
Viscosity @ 40°C	46 cSt

Material Safety Data Sheets are available for all products.  
All reasonable care has been taken to ensure  
that the above information is accurate as of the date of printing.