



36 Draffin Road Hilton, New York 14468
Phone: 585-392-3434
Toll Free: 1-800-828-6351
Sales: sales@monroefluid.com
Technical: technical@monroefluid.com

Monroe Cut 100 CF

Overview

MONROE CUT 100 CF is a cutting oil designed for use in screw machine applications or other machining applications that require the use of neat cutting oils. Monroe Cut 100 CF is chlorine and sulfur free allowing it to be used on a variety of metals including steel, aluminum and brass. MONROE CUT 100 CF is formulated using additives to provide a clean and efficient operating environment, compared to traditional sulfurized cutting oils.

Applications

MONROE CUT 100 CF can be used for centerless grinding, form grinding, creep feed grinding, plunge grinding, belt grinding and flute grinding. MONROE CUT 100 CF can also be used for light machining operations.

Features Benefits

- Low Odor
- Outstanding Lubricity for Superior Finishes
- Low Smoke
- Operator Friendly and Clean Running
- Compatible with all Materials
- Exceptional Cleanliness for Visibility
- Recommended for Screw Machines

Recommended Concentration

Use MONROE CUT 100 CF as received. Do Not mix MONROE CUT 100 CF with water.

Typical Properties

Appearance	Clear Amber liquid
Odor	Bland
Chlorine	Nil
Sulfur	Nil
Viscosity @ 100°F	100 SUS

Material Safety Data Sheets are available for all products.
All reasonable care has been taken to ensure
that the above information is accurate as of the date of printing.