



36 Draffin Road Hilton, New York 14468  
Phone: 585-392-3434  
Toll Free: 1-800-828-6351  
Sales: sales@monroefluid.com  
Technical: technical@monroefluid.com

## Cool Tool II Aerosol

### OVERVIEW

COOL TOOL II Aerosol is a universal cutting and tapping fluid that performs extremely well on ALL metals including Aluminum, Stainless Steel, exotic alloys and some plastics. COOL TOOL II does NOT contain 1,1,1- trichloroethane. COOL TOOL II contains NO ozone depleting chemicals (ODCs).

### APPLICATIONS

Apply COOL TOOL II Aerosol cutting and tapping fluid directly to the cutting tool using a brush, oil can or other convenient applicator. May be used for drilling, tapping, reaming, milling, turning, boring, broaching, hobbing and blanking of all metals.

### MIXING

No mixing is required.

### TYPICAL PROPERTIES

Appearance	Clear Amber liquid
Residual Film	Soft, oily
pH @ 20:1	N/A
Specific Gravity @ 60°F	0.91 ± 0.01
Lbs/Gallon	7.6 ± 0.1
Flash point, PMCC	182° (360°F)

Material Safety Data Sheets are available for all products.  
All reasonable care has been taken to ensure  
that the above information is accurate as of the date of printing.