



36 Draffin Road Hilton, New York 14468  
Phone: 585-392-3434  
Toll Free: 1-800-828-6351  
Sales: sales@monroefluid.com  
Technical: technical@monroefluid.com

## GlasGrind 100

### OVERVIEW

GLASGRIND 100 is an oil free, grinding fluid concentrate containing wetting agents for superior cooling and corrosion inhibitors for in-process rust protection of machine tools and metal parts. When diluted for use, GLASGRIND 100 provides a stable, effective medium for abrasive working of glass and all vitreous materials. GLASGRIND 100 contains a polymer which causes fines to agglomerate and settle rapidly rather than recirculate through the grinding zone. This polymer causes the fines to settle in a soft, easily removed slurry.

### FEATURES & BENEFITS

- Excellent Cooling Function
- Mild Pleasant Odor
- Excellent Corrosion Inhibition
- Long Sump Life
- Allows Soft Settling of Swarf
- Economical
- Oil Free - Minimal Disposal Costs
- Non-Foaming

### APPLICATIONS

GLASGRIND 100 can be used for sawing, drilling, edging, beveling, scratch removal and other abrasive working of glass, plastic, quartz, silica, heat resistant glasses and ceramics. GLASGRIND 100 is compatible with diamond and all other abrasives.

### RECOMMENDED CONCENTRATION

Application	Concentration	Ratio	Refractometer
Flat Glass and Mirror	3% - 5%	1:33 - 1:20	0.6 - 1.1

### MIXING

Concentration	2%	3%	4%	5%
Ratio	1:50	1:33	1:25	1:20
Refractometer	0.4	0.6	0.9	1.1

### TYPICAL PROPERTIES

Appearance-Concentrate	Clear Amber liquid
Appearance - Dilution	Transparent Amber
Residual Film	Soft, soluble
pH @ 20:1	8.7 ± 0.3
Specific Gravity @ 60°F	1.04 ± 0.03
Lbs/Gallon	8.6 ± 0.1
Flash point, PMCC	None

Material Safety Data Sheets are available for all products.  
All reasonable care has been taken to ensure  
that the above information is accurate as of the date of printing.