



MONROE CF RELEASE OIL

General Description

MONROE CF RELEASE OIL is a ready-to-use concrete form release agent specifically designed to be used with wooden concrete forms. The unique blend of mineral oils and fatty acid additives prevent concrete from bonding to the forms, ensuring clean, consistent form release and removal. Wooden form life is extended due to the preservative action of the product.

This product is intended to be used as received, with no mixing or dilution needed. It is not to be mixed with water.

Application

MONROE CF RELEASE OIL may be applied to forms by brushing, spraying, swabbing or other suitable method. Wooden forms should be liberally coated with **MONROE CF RELEASE OIL** prior to first use.

Advantages

- | | |
|--------------------------------------|-------------------------------------|
| • No Residue, Non-staining | • Minimizes Concrete Build Up |
| • Provides Smooth Finish on Concrete | • Prolongs the Life of Wooden Forms |
| • VOC Compliant (<250g/L) | • Sprays Even in Cold Weather |

Mixing Instructions

MONROE CF RELEASE OIL is intended to be used as received, with no mixing or dilution required. **MONROE CF RELEASE OIL** is not dilutable with water.

Typical Properties

Appearance	Clear Amber liquid
Viscosity	9 cSt@40°C (Typical)
Specific Gravity @ 60°F	0.85 ± 0.03
Lbs/Gallon	7.09 ± 0.1
Flash point, TCC	125°C/ 257°F

Packaging

MONROE CF RELEASE OIL is available in 5 gallon pails, 55 gallon drums and 275 gallon IBCs. Safety Data Sheets are available for all products. All reasonable care has been taken to ensure that the above information is accurate as of the date of printing.

36 Draffin Road, Hilton, NY 14468 Phone: 800-828-6351 585-392-3434 Fax: 585-392-2691
sales@monroefluid.com Website: <http://www.monroefluid.com>